


# Rivet Nuts



- ◆ Increases thread engagement in thin metals for an improved metal to metal application.
- ◆ Reduces installation cost by eliminating welding.
- ◆ Knurled body expands 360° to provide exceptional torque and resistance to vibration.

Part Number	Thread Size	Grip Range	Hole Size	L	d <sub>1</sub>	d <sub>3</sub>	k
RN0632420FS-ZD	6-32	.020-.080	17/64	.420	.265	.390	.030
RN0632470FS-ZD	6-32	.080-.130	17/64	.470	.265	.390	.030
RN0832420FS-ZD	8-32	.020-.080	17/64	.420	.265	.390	.030
RN0832470FS-ZD	8-32	.080-.130	17/64	.470	.265	.390	.030
RN1024475FS-ZD	10-24	.020-.130	19/64	.475	.296	.415	.030
RN1024585FS-ZD	10-24	.130-.225	19/64	.585	.296	.415	.030
RN1420580FS-ZD	1/4-20	.027-.150	25/64	.580	.390	.500	.030
RN1420680FS-ZD	1/4-20	.165-.260	25/64	.680	.390	.500	.030
RN5618530FS-ZD	5/16-18	.027-.150	17/32	.690	.530	.685	.035
RN5618685FS-ZD	5/16-18	.150-.312	17/32	.805	.530	.685	.035
RN3816690FS-ZD	3/8-16	.027-.150	17/32	.690	.530	.685	.035
RN3816805FS-ZD	3/8-16	.150-.312	17/32	.805	.530	.685	.035
RN1213115FS-ZD	1/2-13	.063-.200	11/16	1.150	.685	.047	.047
RN1213130FS-ZD	1/2-13	.200-.350	11/16	1.300	.685	.047	.047

Also available in unf and metric threads.

Also available with countersunk head.

## Stafast

Cleveland, OH  
800-782-3278

Charlotte, NC  
800-951-1159

Tupelo, MS  
800-888-6887

Los Angeles, CA  
800-999-9779

Mississauga, ON  
877-782-3278

Visit us on-line at [www.stafast.com](http://www.stafast.com)